

Castrol Transmax Dex III Multivehicle

Automatic Transmission Fluid

Description

Castrol Transmax Dex III Multivehicle, formulated with Smooth Drive Technology™ is designed for use in GM automatic transmissions pre 2005 and Ford automatic transmissions built between 1983 and 1996 where DEXRON® (II or III) or MERCON® are required. This product is approved for use in Allison heavy duty transmissions against TES 389. It is also approved for use in a wide range of european heavy duty automatic transmissions. It may be used in some power steering units.

Transmax Dex III Multivehicle, formulated with Smooth Drive Technology™, delivers enhanced protection and gives drivers a smoother drive for longer.

Advantages

- Multiple manufacturer approvals make it suitable for wide ranging use.
- Enhanced friction durability for smooth transmission performance.
- Enhanced wear and deposits protection to provide longer component life
- Excellent thermal and oxidative stability to effectively resist oxidation and maintains operational efficiency for longer
- High viscosity index provides a stable viscosity over a wide temperature range for effective protection of transmissions and operation of power steering units

Typical Characteristics

Name	Method	Units	Transmax Dex III Multivehicle
Density @ 15C, Relative	ASTM D4052	g/ml	0.859
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.2
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	35
Viscosity Index	ASTM D2270	None	175
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	16500
Pour Point	ASTM D97	°C	-46
Flash Point, COC	ASTM D92	°C	216

Product Performance Claims

Allison C4
Allison TES 389
ZF TE-ML 04D, 14A
MAN 339 Typ Z1
MAN 339 Typ V1
MAN 339 Typ L1
MB-Approval 236.9
Voith H55.6335.xx
Volvo Transmission Oil 97341
Meets Mercon®, Dexron® IIIH, Volvo Transmission Oil 97340

Additional Information

Transmax Dex III Multivehicle is registered under the following ZF approval numbers: ZF000220

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Transmax Dex III Multivehicle
23 Oct 2019
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com