

## Castrol Transmax A CVT

CVT Fluid

### Description

Transmax A CVT, formulated with Smooth Drive Technology™, was developed with and approved by Audi for use in their VL 300 and VL 380 Multitronic (CVT chain) transmission applications. Its superior technology enables longer transmission life. Transmax A CVT, formulated with Smooth Drive Technology™, delivers enhanced protection and gives drivers a smoother drive for longer.

### Advantages

- Exceptional steel on steel friction durability
- Enhanced wear protection that enables longer transmission life
- High shear stability and enhanced antifoaming and air release characteristics maintain effective lubrication throughout the oil drain period.

### Typical Characteristics

Name	Method	Units	Transmax A CVT
Density @ 15C	DIN EN ISO 12185	g/ml	0.841
Appearance	Visual	-	bright & clear
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	39
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	7.63
Viscosity Index	DIN ISO 2909	None	167
Viscosity, Brookfield @ -40C	DIN 51398	mPa.s (cP)	6880
Pour Point	DIN-ISO 3016	°C	-69
Flash Point , COC	ASTM D92	°C	240

### Product Performance Claims

VW TL 52180

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Transmax A CVT

22 Aug 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

[www.castrol.com](http://www.castrol.com)