



Transmax™ DEXRON®-VI

Synthetic Automatic Transmission Fluid (ATF)

Description

Castrol Transmax™ DEXRON®-VI Automatic Transmission Fluid is for use in General Motors vehicles.

Application

Exceeds all passenger car and light truck manufacturer's warranty requirements for vehicles, transmissions or power steering service where a DEXRON®-VI, DEXRON®, DEXRON®-III H, III, IIE and II type ATF is specified.

Advantages

Also satisfies requirements of DEXRON®, DEXRON®-III H, III, IIE and II.
Premium synthetic blend formula exceeds DEXRON®-III H requirements
Enhanced friction durability improves shifting performance
Outstanding sludge resistance provides superior transmission life
Certified and approved by General Motors for all cars and trucks that require DEXRON®-VI.

Typical Characteristics

Name	Method	Units	Typical Value
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	30.2
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	6.1
Viscosity Index	ASTM D2270	None	148
Typical olor	ASTM D-1500		7
Appearance	Visual		Red
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	11,000
Pour Point	ASTM D97	°C (°F)	--54 (-65)
Flash Point, COC	ASTM D92	°C (°F)	177 (351)
Specific Gravity, 60 °F	ASTM-D1298	g/ml	0.846
Pounds per Gallon	ASTM D287		7.03

Product Performance Claims

Approved - GMDEXRON® -VI

Meets - GMDEXRON® -IIE, GMDEXRON® -III, GMDEXRON® -IIIIH

Transmax™ DEXRON®-VI

11 Apr 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com