



Syntrans AT 75W-90

Heavy Duty Manual Transmission Fluid

Description

Castrol Syntrans AT 75W-90 is a synthetic fluid approved for use in the manual transmissions of Mercedes Benz Actros vehicles

Advantages

- Excellent viscosity temperature characteristics providing effective lubrication over a wide temperature range.
- Smooth gear shifting at low temperatures increases transmission efficiency and aids fuel economy.
- Very good wear protection especially under high loads extends component life and reduces downtime and service costs

Typical Characteristics

Name	Method	Units	Syntrans AT 75W-90
Kinematic Viscosity at 100 °C	ASTM D445	mm ² /s	14.1
Kinematic Viscosity at 40 °C	ASTM D445	mm ² /s	99
Brookfield Viscosity @ -40°C	ASTM D2983	mPas	49000
Pour Point	DIN ISO 3016	°C	-42
Flash Point (COC)	DIN 2592	°C	215
Density at 15°C	ASTM D1298	Kg/m ³	844

Product Performance Claims

API GL-4

MB-Approval 235.11

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Syntrans AT 75W-90

04 Sep 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk