



## Seamax Super Plus 15W-40

Multigrade diesel engine lubricant

### Description

Seamax Super Plus 15W-40 is a mineral based High Performance Diesel engine oil specifically selected to meet the lubrication demands of fishing vessels.

### Application

Seamax Super Plus 15W-40 is suitable for use in turbocharged and naturally aspirated engines operating on both gasoline or marine gas oil.

It gives easy cold start and efficient engine lubrication at low temperatures, as well as optimum protection at high temperatures, without increasing oil consumption.

### Advantages

- Superior soot dispersancy.
- Cleaner and more efficient operation.
- Reduced maintenance.
- Excellent oil consumption control.
- Prevention against formation of harmful engine deposits.
- Excellent protection under conditions of extended drain.
- Good viscosity control.

### Product Performance Claims

Seamax Super Plus 15W-40 meets the requirements of API CI-4 Plus.

## Typical Characteristics

Name	Method	Units	Seamax Super Plus 15W-40
SAE Grade			15W-40
Density @ 15°C, Relative	ASTM D4052	g/ml	0.878
Viscosity, Kinematic @ 40°C	ASTM D445	mm <sup>2</sup> /s	113
Viscosity, Kinematic @ 100°C	ASTM D445	mm <sup>2</sup> /s	14.7
Viscosity Index	ASTM D2270	-	134
Viscosity, CCS -20C (15W)	ASTM D5293	cP	5550
Total Base Number, TBN	ASTM D2896	mg KOH/g	10.5
Closed Flash Point	ASTM D92	°C	230
Pour Point	ASTM D97	°C	-12
Ash, Sulphated	ASTM D874	% wt	1.45

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings.

Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Seamax Super Plus 15W-40

04 May 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

[www.castrol.com/marine](http://www.castrol.com/marine)