



Spheerol™AP Range

Bearing Grease

Description

Spheerol™ AP 2 and AP 3 are lithium-based greases incorporating solvent-refined base oils. They contain oxidation and corrosion inhibitors, which help to ensure long service life and a high level of protection for metal surfaces. The greases are water-resistant.

Spheerol AP 2 and AP 3 are mainly intended for use in plain and roller bearings of all types and in all kinds of machinery under normal load conditions and within an operating temperature range of -20 °C to +120 °C.

Application

Spheerol AP 2 and AP 3 are primarily intended for use in plain and anti-friction , ball and roller bearings besides other machinery applications. They are recommended for use under normal load conditions, within an operating temperature range of -20°C to +120°C. Due to the low viscosity used in these products, they are particularly suitable for high speed bearings.

Spheerol AP 3 is suitable for severe vibration conditions.

Advantages

- Corrosion inhibitor additives ensure protection of metal surfaces extending bearing life.
- Oxidation inhibitors extend the life of the grease in high temperature applications minimising the need for re-greasing.
- Water resistance ensures good levels of protection in wet applications.

Typical Characteristics

Name	Method	Units	AP 2	AP 3
Thickener type	-	-	Lithium soap	Lithium soap
Consistency	ISO 2137 / ASTM D217	NLGI Grade	2	3
Colour	Visual	-	Amber/Brown	Amber/Brown
Texture	Visual	-	Smooth & homogenous	Smooth & homogenous
Dropping point	ISO 2176 / ASTM D566	°C/°F	180min/356 min	180 min/356 min
Base Oil Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	100-130	100-130
Worked Penetration (60 strokes @ 25°C / 77°F)	ISO 2137 / ASTM D217	0.1 mm	265-295	220-250
Anti Rust Performance (Emcor)	ISO 11007 / ASTM D6138	Rating	0/1 max	0/1 max
Copper corrosion, 24 hours @ 100°C	ASTM D4048	Rating	1b max	1b max
Oil separation, 168 hours @ 40°C (%)	IP121/ DIN 51817	% wt.	5 max	2 max
Water washout, 1 hour @ 79°C	ISO 11009 / ASTM D1264	%wt loss	10 max	10 max
Flow pressure @ -20°C / -4°F	DIN 51805	mBar	<1400	<1400

Subject to usual manufacturing tolerances.

Spheerol™ AP Range

02 Dec 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrol.com/marine