



Product Data

Aircol 200 Range

Mineral refrigeration compressor lubricants

Description

The Castrol Aircol 200 range of refrigeration lubricants is available as two grades of specially selected mineral oils, highly refined, to provide chemical and thermal stability. Their low wax forming tendencies ensure low pour points.

Application

The Castrol Aircol 200 range is specifically for use in refrigeration and air conditioning plants using fluorcarbon refrigerants. The exceptional low temperature characteristics of these oils prevent the flocculent precipitation of wax which can otherwise occur in high performance plant using Freon refrigerants.

In most systems using R22, the critical solution temperature characteristics of these oils are adequate to prevent oil/refrigerant separation problems within the low temperature circuits. Where evaporation temperatures are exceptionally low or in systems not incorporating oil/refrigerant separators, synthetic base refrigerant oils may be preferred.

Technical Data

Name	Method	Units	Aircol 266	Aircol 299
Density at 15°C	ASTM D4052	g/ml	0.91	0.92
Viscosity at 40°C	ASTM D445	mm ² /s	32	55
Viscosity at 100°C	ASTM D445	mm ² /s	4.1	5.9
Closed Flash Point	ASTM D93	°C	165	183
Pour Point	ASTM D97	°C	-40	-36
Floc Point	DIN 51351	°C	-54	-48

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aircol 200 Range

13 Jun 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

The Technology Centre, Whitchurch Hill, Pangbourne, Reading, RG8 7QR, United Kingdom

+44 (0)203 915 7991

www.castrol.com/globalbusiness