



Product Data

Optigear Synthetic A

High performance fully synthetic gear oil

Description

Optigear™ Synthetic A 320 is a fully synthetic high performance gear oil with MICROFLUX TRANS additives. They offer optimum wear protection under very extreme thermal loads and operating conditions such as vibrations, oscillating motions and shock loads. The wide range of temperature, especially in case of low starting temperatures and the high load carrying capacity are key aspects of this industrial gear oil. Thermally and mechanically stable polyalphaolefin and the MICROFLUX TRANS additive combination adjust themselves to the changing operating conditions and actively prevent wear.

Application

- For especially highly loaded industrial gears - in case of great changes in temperature and extreme loads.
- For wind power stations, conveyor belts, crane control gears, lifts, rolling mills etc.
- For highly loaded eccentrics, gear couplings, chain drives, robot drives and joints as well as positive power transmissions.
- For all types of rolling and sliding bearings, especially for tapered roller bearings in extruders, shaking screens, vibrators or for spindle presses.
- For transport systems operated during winter.
- Especially suited for arctic countries such as Canada, North America and Scandinavia.

Optigear Synthetic A 320 is a CLP-HC gear oil (DIN 51502) and exceed minimum requirements according to DIN 51517 part 3.

Advantages

- Good viscosity/temperature behavior, wide range of operating temperature.
- Excellent low-temperature behavior, easy starting, good fluidity at extremely low temperatures.
- Optimum wear protection - smoothing of pitting and scoring.
- Especially low coefficient of friction leading to reduced friction and energy costs, lowering of oil temperatures.
- Significantly extended oil change intervals, reduced maintenance costs.
- Shear-stable
- High corrosion protection, compatible with non-ferrous metals.
- Compatible with conventional paints and sealing materials.

Typical Characteristics

Name	Method	Units	A 320
Appearance	Visual	-	Dark brown
ISO Viscosity Group	-	-	320
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	870
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D 445	mm ² /s	330
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D 445	mm ² /s	33
Viscosity Index	ISO 2909 / ASTM D2270	-	140
Pour Point	ISO 3016 / ASTM D97	°C/°F	-36/-32.8
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	220/428
Copper corrosion (3 hrs@100°C/212°F)	ISO 2160 / ASTM D130	Rating	1a
SRV Friction and Wear test	ASTM D6425 / DIN 51834	coeff. of friction/ wear scar diam (mm)	0.055/0.50
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	>14
FZG Gear Scuffing test - A/16.6/140	ISO 14635-1 (modified)	Failure Load Stage	>12
FE-8 Bearing Wear test (F.562831.01-7.5/80-80)	DIN 51819-3	roller wear (Mw50)	4.5
FZG Micropitting test @ 60°C/140°F	ASTM D5182 / FVA 54-7	Failure Load Stage/ Micropitting Rating	>10/High

Subject to usual manufacturing tolerances.

Additional Information

- Observe the viscosity specified by the machine manufacturer.
- As Optigear Synthetic A is a highly addivated high performance gear oil miscibility with other gear oils needs to be checked. Maximum performance is only guaranteed if not mixed with any other product.

Optigear Synthetic A

06 Oct 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>