



Product Data

Alpha VT 32

Turbo transmission oil

Description

Castrol Alpha™ VT 32 has been developed specifically for Voith Turbo transmissions to provide long service life and reliability, and has been classified as Voith Index 1 for "enhanced thermal oxidative stability".

Application

Alpha VT 32 is formulated for hydrokinetic transmissions used mainly in railway locomotives and in hydrodynamic turbo couplings, turbo gears and combined turbo-coupling gears. Other applications include trucks and heavy off-highway equipment incorporating this type of transmission unit. The oil is also suitable for conventional industrial gearboxes where a low viscosity oil is suitable. This oil provides higher load carrying performance, together with excellent oxidation resistance, anti-corrosion and minimal foaming.

Alpha VT 32 is fully compatible with nitrile, silicone and fluropolymer seal materials.

Alpha VT 32 meets the requirements of:

Voith Turbo Specification 3.90-8e_2011-07

CLP 32 according to DIN 51517-3

Advantages

- Long service life
- Excellent load carrying and micropitting resistance
- Good seal compatibility
- Low foam and rapid air release
- Excellent demulsification

Typical Characteristics

Name	Method	Units	Alpha VT 32
Density @ 15°C / 59°F	ISO 12185, ASTM D4052	kg/m³	870
Kinematic Viscosity @ 40°C / 104°F	ISO 3104, ASTM D445	mm²/s	32
Kinematic Viscosity @ 100°C / 212°F	ISO 3104, ASTM D445	mm²/s	5.4
Viscosity Index	ISO 2909, ASTM D2270	None	105
Pour Point	ISO 3016, ASTM D97	°C/°F	-42 / -44
Flash Point - open cup method	ISO 2592, ASTM D92	°C/°F	234 / 453
Water Separation @ 54°C / 129°F (40/37/3)	ISO 6614, ASTM D1401	minutes	5
Air Release @ 50°C / 122°F	ISO 9120, ASTM D3427	minutes	4
Foam Sequence I - tendency / stability	ISO 6247, ASTM D892	ml / ml	0 / 0
Foam Sequence II - tendency / stability	ISO 6247, ASTM D892	ml / ml	10 / 0
Foam Sequence III - tendency / stability	ISO 6247, ASTM D892	ml / ml	0 / 0
Rust test - synthetic seawater (24 hrs)	ISO 7120, ASTM D665B	-	Pass
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	>12
FZG Gear Scuffing test - A/16.6/90	ISO 14635-1	Failure Load Stage	12
FZG Micropitting test @ 90°C/194°F	FVA 54/1	Failure Load Stage / Micropitting Rating	>10 (high)
FE-8 Bearing Wear test (F.562831.01-7.5/80-80)	DIN 51819-3	Roller wear (Mw 50), mg	< 10

Subject to usual manufacturing tolerances.

Alpha VT 32

19 Jul 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre, Whitchurch Hill, Pangbourne, Reading, RG8 7QR, United Kingdom

<http://msdspds.castrol.com>