



Product Data

Transmax ATF DEXRON®-VI MERCON® LV Multivehicle

Automatic Transmission Fluid

Description

Castrol Transmax ATF DEXRON®-VI MERCON® LV Multivehicle, formulated with Smooth Drive Technology™, is a Full Synthetic Technology formulation designed for modern automatic transmissions. Its superior technology enables longer transmission life. Transmax ATF DEXRON®-VI MERCON® LV Multivehicle is approved and licenced by GM and Ford for use in vehicles requiring their latest ATF specifications and also exceeds the requirements of the JASO-1A for use in most Asian automatic transmissions. Transmax ATF DEXRON®-VI MERCON® LV Multivehicle is also suitable for use in the majority of 6,7,8 and 9 speed automatics of European cars, meaning it is suitable for use in nearly all passenger car automatic transmissions. It delivers enhanced protection and a smoother drive for longer.

Advantages

- OEM approved and licensed by Ford (MERCON® LV) and GM (DEXRON®-VI)
- Low viscosity formula for maximum fuel efficiency in modern automatic transmissions
- Enhanced friction durability for smooth transmission performance
- Superior high temperature protection to effectively resist oxidation
- Recommended for use in most automatic transmissions

Typical Characteristics

Name	Method	Units	Transmax ATF Dexron-VI Mercon LV Multivehicle
Density @ 15C, Relative	ASTM D4052	g/ml	0.847
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	5.9
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	29.6
Viscosity Index	ASTM D2270	None	151
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	11700
Pour Point	ASTM D97	°C	-51
Flash Point, PMCC	ASTM D93	°C	189

Product Performance Claims

Ford MERCON® LV

GMDEXRON® -VI

Suitable for use where JASO 1A(03)

JASO 1A LV(13) is required including:

Toyota T III, T IV, WS

Mitsubishi SP II, IIM, III, IV

PA, J3

Mazda ATF M-III, M-V, FZ

Honda/Acura DW 1/Z 1

Nissan Matic D, J, S

JWS 3314/3317/ 3309

Suzuki AT Oil 5D06, 2384K

Isuzu

Subaru F6, Red 1

Daihatsu AMMIX ATF D-III

Multi D3-SP

Hyundai/Kia SP III, SP IV

Also suitable for use in 6-speed automatics from Audi BMW, Mini-Cooper, Jaguar, Peugeot/Citroen, Saab, Volvo, VW, Porsche

and all vehicles where Dexron III or Mercon SP is required.

Additional Information

Suitable for use where the following are called for:

JASO M315-2013 1A, 1A LV, 2A

GM DEXRON®-II, DEXRON®-IID, DEXRON®-IIE, DEXRON®-IIIG, DEXRON®-IIIH

Ford MERCON®, MERCON® SP

Aisin Warner JWS 3309 (T-IV), JWS 3324 (WS), AW-1, AW-2

AML Oil No. 4G43A9A509/AA/S , G 055 005

Bentley PY112995PA

BMW JWS 3309 (T-IV), LA2634, LT71141, ETL 7045E, ETL 8072B, ATF 2, ATF 3+, ATF 6, ATF 7

Bosch TE-ML 09

Chrysler ATF+, +2, +3 (MS7176E)

Chrysler/Dodge/Jeep 05127382AA, 6F8043742AA, 68157995AA, 68157995AB, Borg Warner 68049954AA, 68218925AA, 68218925AB

Chrysler/Dodge/Jeep MOPAR SP IV, 68171866AA/68171869AA, NAG1

Daewoo LT 71141

Daihatsu AMMIX ATF D-II, ATF D-III SP

FIAT T-IV type, JWS 3309, 9.55550-AV5, 9.55550-AV6

Ford ATF C-ML5, FNR5 (Mazda M5, XT-9-QMM5), ESP-M2C138-CJ/166-H, WSS-M2C922-A1/924-A (XT-8-QAW) JWS 3309, XL-12

GM TASA, 1940700, 1940767, 21005966, 22717466, 88900925, 9986195, 93160393, Transfer Case (AutoTrak II)

GM/GMC/Opel/Saturn AW1, VI, 88863400, 88863401

Honda ATF-Z1 (except in CVTs), ATF Ultra II, DW-1, Type 3.0, Type 3.1 : 08263-999-01HE, Ultra HEVF-Type 1

Hyundai/Kia ATF RED 1, RED 1K, SP-II, SP-III, SP-IV, SP-IV M, SP-IV M1, SPH-IV, SP-IV-RR, JWS 3314, NWS 9638, 040000C90SG,

ISUZU ATF WSI, BESCO ATF-II, ATF-III, ATF SP, SCS Fluid, 08200-9001

Jaguar ATF, 3403-M115, LT71141, JLM20238, 3403 JLM20238, K17, JLM 20292, Fluid 8432, 02JDE26444, WSS-M2C922-A1

JEEP ATF+3

Land Rover TYK500050, LR0022460, LR023288

Lexus JWS 3309

Maserati 231603

Mazda ATF D-II, M-III, M-V, FZ, A7, F-1, S-1, N-1, 3317

MB 236.10, 236.12, 236.14, 236.15, 236.16, 236.17, 236.41

MINI COOPER T-IV

Mitsubishi Diaqueen SK, SP-II, SP-III, SP-IV, AW, J2, J3, MA1, PA

Nissan Matic Fluid C, D, J, K, P, S, W
 Opel/GM 19 40 700, 19 40 767, 21005966 Transaxle, 22 17466, 88900925, 9986195
 Peugeot/Citroen (PSA) Z 000169756, AL4 Automatic gearbox oil (#9730.AE), 16 350 560 80, B71 2340
 Porsche LT71141, ATF 3403-M115, T-IV (JWS 3309), 000 043 205 09, 999 917 547 00 (A2), 000 043 205 28, Z 000169756
 Renault DPO/AL4, Matic D2, Samsung SATF-D
 Saab T-IV (JWS 3309), 93 165 147, 93 160 393, 45 30 09 800, 93 160 548, Power Steering Fluid 2634
 SsangYong DSIH 5M-66
 Subaru ATF, K0140Y0700, 5AT, HP
 Subaru Opel Original ATF 09117946/93160393
 Suzuki ATF AW-1, 5D06, 2326, 2384K, 3314, 3317, JWS 3309
 Toyota ATF D-II, D-III, T-III, T-IV, WS
 Volvo PN 1161521, 1161540/1161640, 31256774/31256675, PN 1161621
 VW/Audi G 052 025, G 053 025, G 052 162, G 055 025 (JWS 3309), G 052 162 (ZF LifeguardFluid 5), G 055 005 (ZF LifeguardFluid 6), G 055 162 (ZF LifeguardFluid 6 Plus), G 060 162 (ZF LifeguardFluid 8), G 052 990, G 055 540, G 052 055
 VW G 053 001, VW G 055 025 (JWS 3309), VW G 055 540, VW G 052 162 (ZF LifeguardFluid 5), VW G 055 005 (ZF LifeguardFluid 6), VW G 055 162 (ZF LifeguardFluid 6 Plus), VW G 060 162 (ZF LifeguardFluid 8), VW TL 521 62 and TL 52540-A
 ZF TE-ML 09, 11A, 11B
 ZF LifeguardFluid 5, 6, 6 Plus, 7, 8, 9
 ZF LifeGuard Hybrid 2

Also suitable for use in commercial and off-highway applications that require the following specifications:

Allison C-3, C-4, TES-389, TES-468
 Fuso ATF-II, SPIII, A4
 Hino Blue ribbon ATF
 Idemitsu K17 3100 PL085
 MAN 339 Typ A
 Voith 55.6335.xx (G607)
 Volvo CE 97325, 97335, 97340 , 97342 (AT102)
 ZF TE-ML 05L, 21L

Transmax ATF DEXRON®-VI MERCON® LV Multivehicle

01 Jul 2026

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com