



Product Data

Variocut G 408 HC

High performance neat cutting oil

Description

Castrol Variocut™ G 408 HC is a neat cutting oil based on the latest generation of Extreme High Viscosity Index (EHVI) hydrocracked base oils, formulated without chlorinated paraffins.

Variocut G 408 HC can be used in both individual machines and centralised systems.

Application

Variocut G 408 HC is especially designed for hard metal grinding and tungsten carbide grinding with diamond wheels. It can also be used for light duty grinding, drilling and general machining of aluminium and yellow metals and is suitable for spark erosion applications.

In order to maximise product performance, it is recommended that adequate filtration system is used.

	Cast Iron	Low- medium alloyed steel	High alloyed steel / nickel- chromium alloys	Titanium alloys	Aluminum alloys	Yellow metals
Honing/ Superfinishing	ü	ü	ü		ü	ü
Grinding	ü	ü	ü		ü	ü
Drilling					ü	ü
Broaching						
Gear manufacturing						
General machining	ü	ü			ü	ü

Advantages

- Low oil mist and foam characteristics, even at high pressures and flow rates, lead to a reduction in oil consumption and increased production rates
- Superior additive technology leads to very low cobalt leaching tendency, improved grinding performance and cleaner grinding wheels
- Low viscosity and excellent wetting characteristics reduce drag out and result in lower product usage
- Good filtering characteristics and high oxidation stability increase product lifetime
- Our chlorine and heavy-metal free formulation improves the environmental profile and reduces disposal costs
- Low odour, light colour and low mist qualities result in high operator acceptability

Typical Characteristics

Name	Method	Units
Appearance	Visual	
Viscosity at 40°C	DIN 51562	mm²/s
Viscosity at 100°F	ASTM D 446	SUS
Density at 15°C	DIN 51757 ASTM D 1298	
	Calculated	lbs/gal
Flashpoint COC	ISO 2592	°C
	ASTM D 92	°F
Copper corrosion	ISO 2592 ASTM D 130	

Subject to usual manufacturing tolerances.

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Variocut G 408 HC
02 Dec 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<https://msdspds.castrol.com>