



Product Data

Techniclean™ MP

Multi-purpose process cleaner for ferrous metals

Description

Castrol Techniclean™ MP is an aqueous, alkaline industrial multi-purpose cleaner containing biodegradable surfactants and corrosion inhibitors.

Application

Techniclean MP is a multi-purpose process cleaner for precision cleaning of ferrous metals to the most demanding specifications in a wide range of modern equipment, which includes spray and flood wash as well as all types of dip and ultrasonic applications.

Techniclean MP may be used on aluminium with caution: test a sample first to ensure no staining or corrosion, as temperature, concentration and exposure time are all important.

Techniclean MP effectively removes soluble oils, light-medium duty neat cutting or forming oils, lubrication oils, soft film corrosion preventives, swarf and general dirt.

Conditions of Use

	Spray	Flood Wash	Dip	Ultrasonic Dip
Concentration Range:	1 - 5%	1 - 5%	1 - 20%	1 - 20%
Temperature Range:	50 - 65 °C	40 - 65 °C	up to 40 °C	up to 50 °C
Spray Pressure Range:	up to 3 bar	up to 12 bar	n/a	n/a
	up to 50 psi	up to 200 psi	n/a	n/a

Optimum conditions of use are depending on the detailed application requirements and the amount and nature of the soil being removed.

Advantages

- Leaves a temporary corrosion preventive film on the metal surface – minimises scrap rate which improves productivity
- Emulsified oil separates on standing and can be skimmed off in order to increase bath-life – reduces maintenance and disposal cost
- Biodegradable surfactant package – improves environmental profile
- Versatile, can be used in various applications and is suitable in hard and soft water – enables possible product consolidation

Typical Characteristics

Description	Test Method	Unit	Value
Appearance of Concentrate	Visual	-	Clear, light yellow to yellow liquid
Density @ 15 °C	ASTM D4052	g/ml	1.16
pH of Concentrate	ASTM E70-97	-	10.7
pH (3% in Distilled Water)	ASTM E70-97	-	10.3
Cast Iron Corrosion (5% Dilution)	IP 287	-	No stains

Subject to usual manufacturing tolerances.

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer to the product safety data sheet.

Techniclean™ MP

01 Oct 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>