



Product Data

Perfecto HTS 16

Synthetic Heat Transfer Fluid

Description

PerfectoTM HTS 16 is a high-temperature synthetic heat transfer fluid. It has a higher thermal stability than conventional mineral oil heat-transfer fluids, and thus can be used at bulk temperatures up to approximately 20°C / 68°F higher. It has low vapour pressure, high specific heat and high thermal conductivity.

Application

Perfecto HTS 16 is recommended specifically for use in non-pressurized liquid-phase systems that operate at bulk fluid temperatures in the range 320°C - 350°C / 608°F - 662°F, and at maximum film temperature of 374°C / 705°F. (In systems where the bulk temperatures are below 320°C / 608°F, the mineral-based Perfecto HT 5 may be used). Where the expansion-tank temperature exceeds 50°C / 122°F a nitrogen blanket should be employed, to minimize oxidation of the fluid.

Before being commissioned, the system should be pressure-tested for leaks and thoroughly flushed through with Perfecto HTS 16. Under no circumstances should water be used. When the system has become clean, the flushing charge should be drained off and the system filled with Perfecto HTS 16. Careful venting should be carried out while the fluid's temperature is being raised, to remove all air and moisture from the system.

Advantages

- Excellent heat-transfer properties, that can be maintained over long periods of time.
- Very good thermal stability, allowing the fluid to be used at bulk-fluid temperatures of up to 350°C / 662°F.

Typical Characteristics

Name	Method	Units	HTS 16
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	1033
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	14.5
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	2.84
Pour Point	ISO 3016 / ASTM D97	°C/°F	<-21/ <-5
Flash Point - closed cup method	ISO 2719 / ASTM D93	°C/°F	194 / 381
Autoignition temperature	ASTM E659	°C/°F	385 / 725
Specific Heat Capacity (at 200°C / at 350°C)	-	kJ/kg.K	2.16 / 2.60
Thermal Conductivity (at 200°C / at 350°C)	-	W/m.K	0.108 / 0.089
Molecular Weight (Average)	-	g/mol	236
Boiling Point	-	°C/°F	353 / 667

Subject to usual manufacturing tolerances.

Perfecto HTS 16

22 Nov 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>