



Product Data

Molub-Alloy 100-2 HT

Fully Synthetic High Temperature Grease for Long Term Lubrication

Description

MOLUB-ALLOY™ 100-2 HT (previously named Viscotemp™ 2) is a fully synthetic high temperature grease for lubrication points constantly exposed to extremely high temperatures. It ensures long-term lubrication of sliding and rolling bearings and other greasing points at high operating temperatures, elevated bearing pressures and aggressive ambient conditions.

Application

- For rolling and sliding bearings as well as grease-lubricated sliding surfaces in the high temperature range.
- For fan bearings in hot air streams.
- For calender bearings, baking plants and continuous-flow driers.
- In overhead conveyors of painting lines subjected to chemicals.
- For applications with exposure of hot and cold water as well as steam.
- Temperature application range: - 20°C/- 4°F to + 220°C/+ 428°F.

Conditions of Use

- Please follow the specifications of the rolling bearing manufacturers.
- Do not mix with other lubricating greases. In case of doubt please contact the Technical Service.
- Thoroughly clean the bearings before introducing the first fill.
- Fill bearing housing only about half full with MOLUB-ALLOY 100-2 HT.
- Higher temperatures are possible for short-term applications. Please consult our engineers.

Advantages

- Extremely temperature-stable.
- Resistant to hot and cold water.
- Resistant to aggressive ambient influences.
- High protection against friction and wear.
- Excellent load bearing capacity.
- Reliable corrosion protection.
- Silicone-free

Typical Characteristics

Name	Method	Units	Molub-Alloy 100-2 HT
Colour	Visual / ASTM D1500	-	White Yellow ish
Base oil	-	-	PAO/ Ester
Thickner type	-	-	Organic Thickener
Density @ 20°C / 68°F	Inhouse method	kg/m ³	1060
Base Oil Viscosity @ 40°C / 104°F	ASTM D445 / ISO 3104	mm ² /s	120
Dropping Point	ASTM D566 / ISO 2176	°C/°F	>300/>572
Worked Penetration (60 strokes @ 25°C / 77°F)	ASTM D217 / ISO 2137	0.1 mm	265-295
Worked Penetration (100,000 strokes @ 25°C / 77°F) - change from 60 strokes	ASTM D217 / ISO 2137	0.1 mm	15
Water Resistance	DIN 51807-1	Rating	0

This product was previously named Viscotemp 2. The name was changed in 2015.

Molub-Alloy 100-2 HT
24 Dec 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>