



Magna™ SW B Range

Slideway Oil

Description

The Castrol Magna™ SW B Range (previously called Magnaglide™ B grades) are premium slideway lubricants for machine tools.

They are based on highly refined mineral oils and additives to give controlled frictional characteristics in guideway sliding conditions.

Application

The Magna SW B oils are recommended for the high performance lubrication of slideways on machine tools. They have excellent frictional characteristics, high adhesivity, and high film strength, so that they can be used in conditions of high loads and low sliding speeds on both vertical and horizontal guideways.

Furthermore, they can be used for lead screw and nut systems, gears of feed mechanisms and oil lubricated milling heads. The Magna SW B oils meet the criteria of the Schmidt-Coburg friction and demulsibility tests, thus the range has excellent water wash off characteristics.

Advantages

Compared to conventional slideway oils Magna SW B offers the following advantages:-

- Accurate sliding movement leading to enhanced work piece surface finish.
- Excellent protection of slideways for maximum service life of machinery.
- Good wash off characteristics.
- Good compatibility with known construction materials of slideways.
- Conforms to Schmidt-Coburg requirements for friction and demulsibility properties.

Typical Characteristics

Name	Method	Units	SW B 68	SW B 220
Appearance	Visual	-	Clear and Bright	Clear and Bright
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	880	890
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	70	220
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	8.9	19
Viscosity Index	ISO 2909 / ASTM D2270	-	100	98
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	232/450	266/511
Pour Point	ISO 3016 / ASTM D97	°C/°F	-33/-27	-24/-11
Copper corrosion (3 hrs@100°C/ 212°F)	ISO 2160 / ASTM D130	Rating	1b	1b
Rust test - distilled water (24 hrs)	ISO 7120 / ASTM D665A	-	Pass	Pass
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	12	12

Subject to usual manufacturing tolerances.

This product was previously called Magnaglide B Range. The name was changed in 2015.

Magna™ SW B Range

23 Jul 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

PT.Castrol Indonesia, Perkantoran Hijau Arkadia, Tower B, 9th floor. Jl. Let Jend, Simatupang Kav 88, Jakarta 12520, Indonesia

Customer Service: 0807 1 932273

www.castrol.com