



Product Data

Castrol Fork Oil 10W

Suspension Fluid

Description

Castrol Fork Oil 10W is an advanced mineral based suspension fluid designed to provide the optimum damping performance in all on and off road suspensions. Its highly refined basestock and naturally high viscosity index will provide superior anti-fade damping performance over a wide temperature range. Castrol Fork Oil allows air release and anti-fade performance under the most arduous conditions such as found in racing. At low and high speeds there is a minimum suspension unit "stiction" with good operation of suspension units under a wide range of operating conditions.

Application

Castrol Fork Oil is suitable for suspension damper units for on and off road motorcycles. Castrol's mineral Fork Oil range represents a new standard in mineral suspension fluid technology and can be used in all competition and on-road units. By intermixing the grades the optimum suspension fluid can be designed to suit all types of service and load to maximise suspension performance.

Advantages

Castrol Fork Oils are blended with the latest technology performance additives and highly refined base oils to provide:-

- good damping performance over high and low temperatures
- fast air release for anti-fade performance
- wear protection of suspension components
- minimised metal stiction for smooth damping operation
- protection against corrosion of all the internal parts

Typical Characteristics

Name	Method	Units	Castrol Fork Oil 10W
Density @ 15C, Relative	ASTM D4052	g/ml	0.88
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	32
Viscosity Index	ASTM D2270	None	150
Pour Point	ASTM D97	°C	-39
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	6.3
Flash Point, COC	ASTM D92	°C	210

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Fork Oil 10W

03 Mar 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com